



YURATEK

YRT-1000

A professional Approach to Refraction Units

www.yuratek.com

YRT-1000

Refraction Units

TECHNICAL SPECIFICATIONS UNIT AND CHAIR

Unit	YRT-1000
Power	100-110, 220-230 VAC, 50/60 Hz
Electrical Classification	Class I, Type B
Table Top Electrical Output	0-6-12 VAC Dimmable and 100-110, 220-230 VAC, 50/60 Hz
Head Lamp Dimmable	Led Lamp
Maximum Load of Table	20 kg + 20 kg
Chair Carrying Capacity	150 kg
Chair Stroke	180 mm

STANDARD FEATURES

Sliding Table for 2 Instruments
Dimmable Head Lamp
Chart Projector Plate
Safety Knee Switch
Manuel Phorofter Arm
Motorized Chair with Fixed Backrest

CONTROL PANEL


Power On/Off Control
Chair Up/Down Elevation Control
Head Lamp Dimmable Control
Slit Lamp Illumination Light Control

OPTIONAL ACCESSORIES

Autobalance Phorofter Arm
Sliding Manuel Phorofter Arm
Foldable Chair Arm Rest
Foldable Chair Foot Rest
Reading Lamp (Near Vision)
Monitor Support Arm
Triple Trail Lens Drawer (Mobile)
Inclinable Chair Backrest 45°
Inclinable Chair Backrest 180°
Chair Rotation
Manual Horizontal Chair Movement
Chairstroke 200/300/400 mm

Please contact us for customised options, accessories and detailed information.

STANDARD TYPE TECHNICAL DRAWING



TDÜ.720/12.08.2020/REV.T.02.09.2024/02

Optional Drawer Type



IMPORTANT Yuratek Ltd. Şti. subject to change in design and / or specifications without advanced notice. For detailed info please contact your dealer.